MARKED-UP VERSION

2

IN THE CLAIMS:

Please amend the claims as follows:

1. -19 (Cancelled)

20. (previously presented) A supporting sleeve for a body stump, said supporting sleeve having at least a distal end and an open receiving end, namely a liner, comprising:

a sleeve member having an inner surface defining a concave shape proximate said distal end for bounding at least a portion of said body stump during a use thereof;

said sleeve member being at least partially an elastic and an electrically insulating material along said inner surface;

said sleeve member further comprises a first portion electrically conductive layer proximate said distal end and a second portion electrically conductive layer being spaced from said inner surface by at least a portion of said elastic and electrically insulating material of said sleeve member along said open receiving end; and

means for forming a electrically conductive region between said first and second portions of and said electrically conductive layer including a liner cup member at said distal end of said sleeve member.

21-23. (canceled)

24. (previously presented) A supporting sleeve for a body stump, according to claim 20, wherein: said liner cup member is one of a cup member formed from an electrically conductive material and a cup member coated with an electrically conductive material, whereby said liner cup member is in an electric communication with said electrically conductive layer.

AMENDMENT 3 MERTE.Y3-17

In Re Application of Christoph KURTH

25. (previously presented) A supporting sleeve for a body stump, according to claim 20 wherein:

a measured electrical resistance between said surface and said conductive region is less than about 10^5 ohms.

26. (previously presented) A supporting sleeve for a body stump, according to claim 20, further

comprising:

means for enabling a secure connection between said supporting sleeve and an external

prosthesis shaft member.

27. (previously presented) A supporting sleeve for a body stump, according to claim 26, further

comprising:

said means for enabling a secure connection being one of an electrically conducting means

and an electrically insulating means.

- 28. (canceled)
- 29. (canceled)

30. (previously presented) A supporting sleeve for a body stump, according to claim 20, wherein:

said electrically conductive layer includes at least one of an electrically conductive

elastomeric material, an electrically conductive textile material, electrically conductive threads of

graphite, an electrically conductive metallic material, and electrically conductive plastic material.

31. (previously presented) A supportive sleeve for a body stump, according to claim 20, wherein:

said electrically conductive layer is a matrix of an electrically conductive material enclosed

by an elastic material.

In Re Application of Christoph KURTH

- 32. (canceled)
- 33. (canceled)
- 34. (currently amended) A supportive member, according to claim [[33]] <u>36</u>, wherein: said electrically conductive layer includes a matrix of an electrically conductive material enclosed by an elastic material.
- 35. (previously presented) A supportive member, according to claim 34, wherein: said matrix is at least one of an ordered and a disordered assembly of thread members of an electrically conductive material.
- 36. (currently amended) A supportive member, according to claim 33, configured to conform to an external stump further comprising:


a supportive concave sleeve having an inner surface defining a receiving concave shape having an inner distal end and an opposing outer open non-distal end;

said supportive concave sleeve being an elastic electrically insulating material;

a partially rigid liner member in said supportive concave sleeve having a first portion and a second portion;

said first portion of said liner member being electrically conductive and being on said inner surface of said concave sleeve at said distal end thereof opposite said non-distal end;

a second portion of said liner member having a concave shape and being electrically conductive and extending away from said first portion within an inner portion of said supportive concave sleeve, whereby said second portion is electrically conductive with said first portion but is spaced from said inner surface of said elastic insulating material of said sleeve and electrically separated there from;



37. (previously presented) A supportive member, according to claim 36, further comprising: means for enabling an electrical connection between said conductive cup member and an external prosthesis member.